



## 2 Seats Moke

As the professional engineering vehicles and new energy vehicles manufacture, we would like to provide you Hilima 2 seats MOKE .Its products are well-known at home and abroad for their durability and excellent performance. We exported our products to more than 30 countries with strong technical support, good quality and services.

## 1. Product introduction of the 2 SEATS MOKE

2 seats MOKE is the competitive product of our company, which follows the century-old classic and is the perfect return of a century-old classic model.

- All chassis and body are aluminum manganese alloy lightweight design.
- 2 SEATS MOKE has been certified by the EEC of the European Union and DOT of the United States
- 2 seats MOKE has high - low automatic switch of the two - speed transmission, so that the car climbing is more powerful, high-speed is more stable.
- 2 seats MOKE uses electronic self - brake system, which is safer and more efficient.
- 4 KW AC motor, strong power, high efficiency for low speed vehicle.

## 2. Product parameter of the 2 seats MOKE

Measurement Parameter

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

(L*W*H)	2480*1530*1550 mm
Wheelbase	1630 mm
Wheel track front/rear	1250mm/1350mm
Ground Clearance	180mm
Max climbing ability	23°
Curb Weight	330Kg
Full load	860Kg
Range	120Kms
Seats	2

### 3. Product feature and application of the 2 seats MOKE

Type	600cc\Water-cooled\8 valves.\L2 \ EURO 5 EMISSION
Bore*Stroke (mm)	72*72
Compression Ratio	9.8
Max. Power ( kw /rpm)	25/5500
Max. Torque ( Nm/rpm)	52/3000--3500
Fuel Supply System	MPFI
Max. Speed km/h	85
Starting	Electric
Min stable speed (rpm)	1000±50

Min fuel consumption (g/ kw.h)	265
Ignition type	Inductance discharge type
Spark plug modle	LDK7RTC
Distribution type	DOHC
Lubrication type	Pressure spray lubrication
Lubricating oil pump type	Rotor type oil pump
Lubricating oil label	10W-30 SAE
Lubricating oil capacity	1.5-2.2L
Clutch type	Dry-type monolithic clutch
Engine dimension(LXWXH)	404*418*563 mm
Engine weight	61kg
Transmission	Automatic
Drive Train	Front engine, Front drive
Dimension	
L*W*H	3180*1450*1550
Wheelbase	2050mm
Fuel tank Capatity	40L
Ground clearance	200mm
Min turning radius	9 m
Dry Weight	560KG
ChassisSystem	ALUMINUMFRAME

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

Braking system (F/R)	Disc Brake (F/R)
Suspension System (F/R)	McPherson independent suspension
Tires/Front/Rear	155/65R13



In the seaside, in the grassland, in the beautiful scenic spots, there are her beautiful figure.



A wonderful car for festive revelry



We are in the same club





Sea and sky, I am the most beautiful guy

## Detailed parameters

Dimension (L*W*H)	2480mm×1520mm×1550mm
Weight of vehicle(with battery)	677 kg
FRAME	Aluminum Frame
Min ground clearance	150mm
Rated member	2person
Wheelbase	1630 mm
Track Tread(F/R)	1250/1350mm
Brake Type(F/R)	Disc/ Disc
Brake system operating type	Pedal brake

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: [zlh7611@hotmail.com](mailto:zlh7611@hotmail.com)

Rim type (F/R)	13×5.5
Tire size (F/R)	155/65R13
Tire pressure (F/ R )	250Kpa
Max. Speed	45Km/h
Economical speed	35Km/h
Brake distance	≤18m when fully loaded& speed under 45 Km/h
Climbing ability	Gradient 23%
Min Round radius	≤10m
Rated power of driving motor	4KW
Type of driving motor	AC Brushless
Nominal battery voltage	72V
Specification/ quantity of battery	12V-120Ah/ unit×6 units
Type of battery	Lead-acid gel maintenance-free battery
Weight of battery	240 KGS
Charger specification	input voltage: AC220V~240V
Per Charging time	8-10h

